



SPECIFICATION

Model	HI-P5DKGL10X
Camera	
Image Sensor	1/2.5" Aptina CMOS Sensor
Horizontal Resolution	5MP
Compression	H.264/H.265
Minimum Illumination	Color: 0.008 Lux @ (F1.6, AGC ON),B/W: 0 Lux with IR
S/N Ratio	60db
WDR	120dB
PTZ	
Horizontal Rotation Speed	30°/sec
Horizontal Rotation Range	0°~180°
Tilt Rotation Speed	25°/sec
Tilt Rotation Range	-45°~40°
Preset Points	255
Guard Tours	8 groups
Guard Points	Max 20 points
Lens	
Focus Length	5.1-51mm F2.36-F2.4
Focus Control	10X Optical Zoom
Night Vision	
Infrared LED	Ø 35x4PCS + 2PCS LED Laser
IR Range	100m

Day-night mode	AUTO
Network	
Network protocol	TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP,RTCP,NTP,SMTP
ONVIF	Support (PROFILE S,PROFILE G,PROFILE T)
Network interface	Built-in RJ45 network interface,support 10M/100M IP DATA
Main Stream1	5MP(2592*1944)@15fps
Main Stream2	4MP(2560*1440)@15fps
Main Stream3	1080P(1920*1080)@30fps
Main Stream4	720P(1280*720)@30fps
Main Stream5	N/A
Main Stream6	N/A
Sub Stream1	D1(720*480)@15fps
Sub Stream2	CIF(352*288)@15fps
Sub Stream3	N/A
Sub Stream4	N/A
AI Function	
Intelligent Analysis	/
Interface	
Audio	/
Audio Encode	G711A, C711U
Alarm	N/A
SD Card Slot	N/A
POE	YES
General	
Weatherproof	IP66
Operating Temperature	Indoor: 0°~ +40° Outdoor: -40°~ +60°
Operating Humidity	≤90% Non Condensing
Power	DC12V/2A
Lightning Protection	Transient voltage 6000V
Dimension	39.6x19.6x16(cm)
Weight	1.35Kgs

