



## SPECIFICATION

|                           |                                                      |
|---------------------------|------------------------------------------------------|
| Model                     | HI-PD5DASS4X                                         |
| <b>Camera</b>             |                                                      |
| Image Sensor              | 1/2.5" Aptina CMOS Sensor                            |
| Horizontal Resolution     | 5MP                                                  |
| Compression               | H.264/H.265                                          |
| Minimum Illumination      | Color: 0.008 Lux @ (F1.6, AGC ON),B/W: 0 Lux with IR |
| S/N Ratio                 | 60db                                                 |
| WDR                       | 120dB                                                |
| <b>PTZ</b>                |                                                      |
| Horizontal Rotation Speed | 25°/S                                                |
| Horizontal Rotation Range | 0°~350°                                              |
| Tilt Rotation Speed       | 20°/S                                                |
| Tilt Rotation Range       | 0°~70°                                               |
| Preset Points             | 220                                                  |
| Guard Tours               | 3 groups                                             |
| Guard Points              | Max.16 points                                        |
| <b>Lens</b>               |                                                      |
| Focus Length              | 2.8mm-12mm                                           |
| Focus Control             | 4X Optical Zoom                                      |
| <b>Night Vision</b>       |                                                      |
| Infrared LED              | Ø 35x4PCS                                            |
| IR Range                  | 35M                                                  |

|                       |                                                                 |
|-----------------------|-----------------------------------------------------------------|
| Day-night mode        | AUTO                                                            |
| <b>Network</b>        |                                                                 |
| Network protocol      | TCP/IP,ICMP,HTTP,HTTPS,FTP,DHCP,DNS,DDNS,RTP,RTSP,RTCP,NTP,SMTP |
| ONVIF                 | Support (PROFILE S,PROFILE G,PROFILE T )                        |
| Network interface     | Built-in RJ45 network interface,support 10M/100M IP DATA        |
| Main Stream1          | 2560*1920@15fps                                                 |
| Main Stream2          | 2560*1440@15fps                                                 |
| Main Stream3          | 2304*1296@15fps                                                 |
| Sub Stream1           | 800*448@15fps                                                   |
| Sub Stream2           | 704*576@15fps                                                   |
| Sub Stream3           | 352*288@15fps                                                   |
| <b>AI Function</b>    |                                                                 |
| Intelligent Analysis  | /                                                               |
| <b>Interface</b>      |                                                                 |
| Audio                 | /                                                               |
| Audio Encode          | G711A, C711U                                                    |
| Alarm                 | N/A                                                             |
| SD Card Slot          | N/A                                                             |
| POE                   | YES                                                             |
| <b>General</b>        |                                                                 |
| Weatherproof          | IP66                                                            |
| Operating Temperature | Indoor: 0°~ +40° Outdoor: -15°~ +60°                            |
| Operating Humidity    | ≤90% Non Condensing                                             |
| Power                 | DC12V/2A                                                        |
| Lightning Protection  | Transient voltage 3000V                                         |
| Dimension             | 14x14x13(cm)                                                    |
| Weight                | 1100g                                                           |